

Art. 014-1087-032

Quick coupler Meclube-Lock

With hardened 4-jaws made of tool steel
 With high performance hydraulic-gasket
 Uncoupling over 600 bar is possible
 Swivelling joint with thread M 10x1 mm
 Coupler length 32 mm

Supplied in blister packaging



014-1087-032

Art. 014-1087-081

Quick coupler Meclube-Lock-L

With hardened 4-jaws made of tool steel
 With high performance hydraulic-gasket
 Uncoupling over 600 bar is possible
 Swivelling joint with thread M 10x1 mm
 Coupler length 81 mm

Supplied in blister packaging



014-1087-081

THE ADVANTAGES OF THE Meclube-Lock COUPLER

1. Simple activation

To activate the coupler you only have to press the lever with the thumb and insert it on the grease gun.
 The hardened 4-jaws maintain the coupler firmly inserted.



2. Simple release

After you have finished the greasing process, you have to press the lever with the thumb to pull out the coupler from the grease gun.



3. Free hands

Once you have activated the coupler, it remains firmly inserted so there is no need to keep it fixed. Its extreme stability allows you to complete the operation with free hands.



4. Universality

Its special design allows to use it with all the grease guns configurations: SAE, DIN, BS, etc.

Art. 014-1087-000

Meclube-Lock display box

Composed bay:
 30 pcs quick couplers Meclube-Lock length 32mm

Supplied in blister packaging



014-1087-000