

SWIVELLING AUTOMATIC HOSE REELS IN PAINTED STEEL FOR DIESEL 10 bar

Equipped with:

- Black antistatic rubber hoses
- Galvanized steel connections
- Galvanized steel - anodized aluminum 90° swivelling joint
- Viton® seals

Article	Capacity	L. hose	Ø hose	Inlet-Outlet
071-1308-500	80 l/min	without hose	-	F1" G - M3/4" G
071-1308-508	80 l/min	8 m	3/4" - 19x27	F1" G - M1" G

S-460



Article	Capacity	L. hose	Ø hose	Inlet-Outlet
071-1408-600	95 l/min	without hose	-	F1" G - M1" G
071-1408-510	90 l/min	10 m	3/4" - 19x27	F1" G - M1" G
071-1408-515	85 l/min	15m	3/4" - 19x27	F1" G - M1" G
071-1408-610	95 l/min	10m	1" - 25x35	F1" G - M1" G

S-550



Article	Capacity	L. hose	Ø hose	Inlet-Outlet
071-1508-600	95 l/min	without hose	-	F1" G - M1" G
071-1508-520	83 l/min	20 m	3/4" - 19x27	F1" G - M1" G
071-1508-615	90 l/min	15 m	1" - 25x35	F1" G - M1" G

S-555



OVERALL DIMENSIONS SWIVELLING VERSION

Mod.	A	B	C	D	E	F	G	H
S-460	150	120	168	196	95	490	460	575
S-550	200	150	225	270	120	572	550	680
S-555	250	200	225	270	170	572	550	680

