

INDUSTRIAL HOSE REELS IN PAINTED STEEL MOTORIZED 230V ELECTRIC SERIES Mod. FE-600



FE-601

For air-water and diesel 20 bar

Equipped with:

- Brass swivelling joint - Viton® seals
- **Electric 230V AC motor** 448W power

Article	Model	Internal reel width	Inlet-Outlet
076-6132-600	FE-601	330 mm	F1" - F1" BSP
076-6232-600	FE-602	440 mm	F1" - F1" BSP
076-6332-600	FE-603	550 mm	F1" - F1" BSP

For water 150° C 200 bar

Equipped with:

- AISI 304 stainless steel 90° swivelling joint - Viton® seals
- **Electric 230 AC motor** 449W power 448W power

Article	Model	Internal reel width	Inlet-Outlet
076-6135-600	FE-601	330 mm	F1" - F1" BSP
076-6235-600	FE-602	440 mm	F1" - F1" BSP
076-6335-600	FE-603	550 mm	F1" - F1" BSP

For oil and lubricants 250 bar

Equipped with:

- Galvanized steel swivelling joint - NBR seals
- **Electric 230V AC motor** 448W power

Article	Model	Internal reel width	Inlet-Outlet
076-6136-600	FE-601	330 mm	F1" - F1" BSP
076-6236-600	FE-602	440 mm	F1" - F1" BSP
076-6336-600	FE-603	550 mm	F1" - F1" BSP

For grease 300 bar

Equipped with:

- Galvanized steel swivelling joint - NBR seals
- **Electric 230V AC motor** 448W power

Article	Model	Internal reel width	Inlet-Outlet
076-6137-600	FE-601	330 mm	F1" - F1" BSP
076-6237-600	FE-602	440 mm	F1" - F1" BSP
076-6337-600	FE-603	550 mm	F1" - F1" BSP

Hose reel capacity

Ø Hose	Ø external Hose	Mod.FE-601	Mod.FE-602	Mod.FE-603
1/2"	20 mm	50 m	100 m	200 m
3/4"	27 mm	30 m	60 m	90 m
1"	34 mm	20 m	40 m	60 m

Overall dimensions

Model	A	B	C	D	E	F	G	H	I	J	Weight	Packaging
FE-601	660	733	600	530	100	350	550	330	580	810	114 kg	800X1200X950 mm
FE-602	660	733	600	640	100	350	550	440	690	920	119 kg	800X1200X950 mm
FE-603	660	733	600	750	100	350	550	550	800	1030	124 kg	800X1200X950 mm



FE-602



FE-603

